

XIII INTERNATIONAL WINTER ROAD CONGRESS

QUÉBEC, FEBRUARY 8 TO 11, 2010



Québec

SUSTAINABLE WINTER SERVICE FOR ROAD USERS

ROAD HEATING USING HOT SPRING WATER AS THE RENEWABLE HEAT SOURCE

Hidenori Mogi

City of Sapporo, Japan

Chief, Snow Removal Planning Section, Snow Management Office, Construction Bureau

Hidenori.mogi@city.sapporo.jp



OUTLINE

1. INTRODUCTION

2. LOCATION, CLIMATE AND SNOW REMOVAL OF SAPPORO

3. RENOVATION PROJECT IN THE JOZANKEI DISTRICT

4. NEW DIRECTIONS FOR ROAD HEATHING

5. CONCLUSION



ABOUT SAPPORO CITY

- Overview of Sapporo

Topography 43 °N. latitude 141 °E. longitude

Population 1.9 million





CLIMATE OF SAPPORO

- Weather conditions

Avg. annual temp. 8.5 °C



130 winter days48 frost days

Annual snowfall: 6 m





WINTER ROAD MAINTENANCE OF SAPPORO

- Winter road maintenance

Length of roads maintained 5,400 km (trunk roads: 840 km)

Sidewalk snow removal 2,900 km

Annual snow removal budget \$143 million or €102 million





WINTER ROAD MAINTENANCE OF SAPPORO

 During city-wide snow removal About 1,000 machines operate. About 3,000 people work. The cost is \$1.2 million (€85 thousand).

- Amount of snow hauled about 8,000,000 m³







WINTER ROAD MAINTENANCE OF SAPPORO

- Anti-freezing measures

Spreading of de-icing agents or sand

Road heating systems

Energy source	Number of systems	Coverage (m ³)
Electric	366	166,411
Gas	75	32,511
Other	2	7,995







- The Jozankei hot spring district A popular retreat

25 km southwest of downtown270 m above sea level2.5 °C colder than downtown

Steep and narrow roads



- Japan's first road heating system using hot spring water



- Renovation project

Length: 650 m Width: 12.5 m (roadway: 6.5 m) (sidewalk: 3 m×2)

Pitch difference 20 m Steepest gradient 10%





- Chronology of Jozankei's road heating system
 - 1966: Road heating is installed on Jozankei Chuosen St. (the first road heating in Japan).
 - 1984: The system is converted to a heat pipe system (complete overhaul).
 - 1998: Renovation is requested by the local community.
 - 2004: Talks with local residents start.
 - 2008: The improvement project starts.



0: The project is scheduled to be completed in this year.

- The hot spring

A natural spring: 600 *l*/min Temp.: 80 °C

- Design conditions

Snowfall density	3 cm/hr
Air temp.	-10 °C
Snow density	50 kg/m ³
Wind velocity	3 m/sec
Heat load	207 W/m ²



- Cross-section (before renovation)

Cross-section of the former installation





- Cross-section (after renovation)





Polybutylene pipes

Completed phase







- Landscape planning

The project was discussed with hotel owners for 3 years.

Rectangular granite flagstones are to be used.

Street lamps are to create a Japanese spa atmosphere.

Trees that epitomize Jozankei are to be used.





NEW DIRECTIONS FOR ROAD HEATHING

- Pervasion of studless tires





The emergence of very slippery road surface





The distant mountain range is visible without road dust

NEW DIRECTIONS FOR ROAD HEATHING

- Road surface conditions

Regular management

New management criteria: Increased anti-freezing application and more frequent snow removal





NEW DIRECTIONS FOR ROAD HEATHING

Number of road heating systems and total coverage



CONCLUSION

- Reduction in heating costs is very important.
- Jozankei is an exception because a renewable, inexpensive energy source is used.
- We continue to develop safer, more effective winter road maintenance measures.



